



---

## **PR-N3221**

# **2 Mils, 11 Ounce Surface Protection Polyethylene Film**

PR-N3221 is a 2 mils co-extruded polyethylene film coated with a special acrylic adhesive. UV resistance is 120 days in all weather.

### **Application**

- Temporary protection of satin aluminum, embossed pre-painted metal and laminated plastic
- Eliminates scratches, scuff marks and dirt on your finished products

### **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

### **Sizes**

10", 16" , 22.75" x 600'

## Technical Data

Carrier	Co-Ex Film
Adhesive	Acrylic
Thickness	2 mils
Carrier Thickness	1.8 mils
Adhesion	11 oz/in
Elongation	550% - Long / 780% - Trans
Unwind Force	2 oz/in

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.