

RE-T6702

Double Coated Repulpable Tape For Flying Splices

RE-T6702 is a double coated repulpable tape coated with a light green, water soluble acrylic adhesive. RE-T6702 exhibits very high wet grab.

Application

- Recommended for high speed automatic splicing on newsprint offset, web, flexographic and rotogravure printing.

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

Sizes

12 mm x 33 m

18 mm x 33 m

24 mm x 33 m

Technical Data

Carrier	Non-Woven Paper
Adhesive	Light Green, Water Soluble Acrylic
Release Liner	Silicone Coated Glassine Paper
Total Thickness	3.94 mil
Adhesion	Wood Free Paper: 50.3 oz/in / Steel Panel: 57.1 oz/in

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.